

SPECIFICATION



SPECIFICATION FOR THE USE OF BIOCHECK ALLWEATHER

SURFACE PREPARATION

1. Ensure all surfaces are sound, dry, clean and free from dirt, oil, grease or other contaminants. Treat moss, lichen and algae growth with LICHENITE in accordance with instructions. For heavy contaminations use high pressure water jetting to remove growths. Leave 24 hours before proceeding.
2. Cracked and damaged surfaces to be repaired with suitable exterior grade proprietary filler.
3. Stir BIOCHECK ALLWEATHER Pliolite® resin-based masonry paint thoroughly before use. Apply liberally by brush, roller, conventional or airless spray.
4. Porous and Powdery Surfaces – Brush apply first coat thinned with up to 15% of white spirit per 5 litres by volume. Follow with one or two full coats of BIOCHECK ALLWEATHER Pliolite® resin-based masonry paint as required to obtain full obliteration.
5. Non porous, sound surfaces – Brush, roller, conventional or airless spray apply two coats of BIOCHECK ALLWEATHER Pliolite® resin-based masonry paint undiluted.

Spray: Can be thinned with up to 5% of white spirit by volume per 5 litres of paint.

APPLICATION NOTES

Covering capacity:	Dependent upon substrate profile and suction, typically: Porous/textured surfaces: 3-4 ² m per litre Non-porous surfaces: 6-8 ² m per litre
Drying time:	Touch dry in 1 hour, recoat 16 hours.
Colours:	White, Magnolia, Cream, Parchment, Maltese Stone, Dewdrop, Ivory, Peanut Butter, Summer Blue, Terracotta and Seagull.
Cleaning:	Clean brushes, rollers and spray equipment immediately after use with white spirit.
Availability:	Supplied in 5 litre containers.
Storage:	Ensure the container is stored upright and secure at all times. Protect from frost and extremes of temperature. Keep out of direct sunlight.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

IMPORTANT NOTICE

It is essential that when using any type of chemicals, whether they are disinfectants, washing detergents or mould treatments, that all vulnerable people, children, pets and animals are kept away from the materials and the areas being treated, until they are dry. In addition, any spillage of chemicals must be cleaned up immediately before proceeding further with the work.

Store chemical products in original container, in a safe place away from children and pets

MOULD GROWTH CONSULTANTS LTD

Unit A3 Longmead Business Centre, Blenheim Road, Epsom, Surrey KT19 9QQ. Tel: 01372 743334