

SPECIFICATION



SPECIFICATION FOR THE USE OF HALOSEAL

Surfaces should be sound, clean and as dry as possible, and faults/cracks in the structure should be rectified.

1. Moss, lichen and algae growths must be treated using LICHENITE in accordance with MGC specification.
2. Loose and friable materials should be removed by stiff bristle (not wire) brushing. DETERGENTS must not be used in washing down or other surface preparation.
3. Protect all glazing and mask as required. Masking tape must be removed before HALOSEAL becomes dry. Shake container before use – **DO NOT DILUTE** or mix with other products.
4. Apply one coat of HALOSEAL liberally by brush or low-pressure spray, (not airless spray), until suction/absorbency of substrate is satisfied. If applying a second coat, allow a minimum of one hour and a maximum of four hours between coats. It is essential that the second coat is applied before the first coat has fully dried.

APPLICATION NOTES

Do NOT apply in wet or frosty weather or when there is a risk of same during drying time.

Drying time is dependent upon temperature, humidity and absorbency of substrate, normally 6 to 12 hours. Clean brushes and spray equipment immediately after use and remove any splashes or over-spray with white spirit.

It is recommended that on very porous surfaces a second coat of HALOSEAL be applied to ensure long-term protection. A second coat must be applied before the first coat is fully cured/wet on wet. Balcony and garden walls must be treated both sides and soldier courses/coping stones should receive two coats.

HALOSEAL may be over-painted after 4-6 months with BIOCHECK SP masonry paint.

HALOSEAL should NOT be used on painted surfaces or high density/low suction substrates such as glazed bricks, faience tiles and engineering bricks.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

IMPORTANT NOTICE

It is essential that when using any type of chemicals, whether they are disinfectants, washing detergents or mould treatments, that all vulnerable people, children, pets and animals are kept away from the materials and the areas being treated, until they are dry. In addition, any spillage of chemicals must be cleaned up immediately before proceeding further with the work.

Store chemical products in original container, in a safe place away from children and pets.