

# SPECIFICATION



## **SPECIFICATION FOR THE USE OF HALOSTAIN TC**

HALOSTAIN TC is a deep penetrating stain which provides water shedding and resistance to decay, algae and natural greying for rough sawn timber.

1. Preparation: Minimum preparation is required. Timbers should be stiff brushed free of dirt and debris. Kill algal growths with LICHENITE, used in accordance with manufacturer's guidelines.
2. Stir thoroughly prior to application and periodically during use.
3. Application: Normally by brush but can be sprayed using low pressure spray (not airless) equipment.
4. Avoid contaminating garden plants and fishponds.
5. **HALOSTAIN TC should NOT be used on below ground timbers.**

### **APPLICATION NOTES**

When spraying, slight extra dilution with water may be required.

DO NOT apply in wet or frosty conditions or when there is a risk of same during drying.

Application is preferable to dry timber but slightly damp timbers can be treated successfully. HALOSTAIN TC is recoatable in 1-3 hours in normal drying conditions.

**AVAILABILITY:** Supplied in ready-to-use form in 5 litre containers in deep chestnut.

**CLEANING:** Clean equipment in water.

**SHELF LIFE:** 18 months in an unopened container.

**DRYING TIME:** 1-3 hours depending on conditions.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

### **IMPORTANT NOTICE**

It is essential that when using any type of chemicals, whether they are disinfectants, washing detergents or mould treatments, that all vulnerable people, children, pets and animals are kept away from the materials and the areas being treated, until they are dry. In addition, any spillage of chemicals must be cleaned up immediately before proceeding further with the work.

Store chemical products in original container, in a safe place away from children and pets.

**MOULD GROWTH CONSULTANTS LTD**

Unit A3 Longmead Business Centre, Blenheim Road, Epsom, Surrey KT19 9QQ. Tel: 01372 743334