

SPECIFICATION



SPECIFICATION FOR THE USE OF LICHENITE

One coat application gives a coverage of 4-8 square metres per litre, depending on the extent of growth and porosity of the surface.

LICHENITE should be applied liberally by low pressure spray or large paint brush. Allow to react for 72 hours, after which time the dead growth should be removed with a stiff bristle brush or broom.

In areas of heavy contamination a second coat of LICHENITE should be applied after the growths have been removed.

Large areas of growth should be removed first by power washing. The substrate should then be treated with LICHENITE to kill the roots.

The effectiveness of the treatment under normal conditions is approximately 5 years but this is considerably extended by the use of HALOSEAL, ROOFCOAT FR10, BIOCHECK ALLWEATHER, BIOCHECK SP or HALOSTAIN.

Do not apply LICHENITE during periods of hot sunshine, frost or wet weather. Growing plants should be protected from over-spray. If spillage or over-spray occurs, wash off with plenty of clean water.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

IMPORTANT NOTICE

It is essential that when using any type of chemicals, whether they are disinfectants, washing detergents or mould treatments, that all vulnerable people, children, pets and animals are kept away from the materials and the areas being treated, until they are dry. In addition, any spillage of chemicals must be cleaned up immediately before proceeding further with the work.

Store chemical products in original container, in a safe place away from children and pets.

MOULD GROWTH CONSULTANTS LTD

Unit A3 Longmead Business Centre, Blenheim Road, Epsom, Surrey KT19 9QQ. Tel: 01372 743334